

[ [TM-800](#) ] [ [TM-833](#) ] [ [TM-600](#) ] [ [TOP-I](#) ] [ [TOP-II](#) ] [ [PRO-I](#) ] [ [PRO-II](#) ] [ [PRO-A](#) ] [ [TM-979](#) ]  
[ [TM-700](#) ] [ [TM-989](#) ] [ [TM-808](#) ] [ [TM-818](#) ] [ [TM-868](#) ] [ [TM-621](#) ] [ [TM-633](#) ] [ [TM-326](#) ]

## TM-326



### Key Specifications/Special Features:

Type: dynamic

Directivity: unidirectional

Output sensitivity: -72 +/- 3dB

Output impedance: 600 ohme +/- 30%

Frequency response: 100 to 10,000Hz

Cord: (diameter) 5.5mm x 5m

Dimensions: (diameter)53 x 179mm

[HOME](#) \ [COMPANY](#) \ [PRODUCTS](#) \ [NEWS](#) \ [E-CATALOG](#) \ [CONTACT US](#)

No 68. SanGuan 1st. Taichung City, Taiwan

Tel: +886 (4) 22342388 Fax: +886 (4) 22337166 E-mail Address(es): [tev@tev.com.tw](mailto:tev@tev.com.tw)

Copyright Taiwan Electric Voice Co. Ltd. Taiwan Products, B2BChinaSources, B2BManufactures